


NOTES:


- 1. THE NAME OF THE MANUFACTURER AND DIRECTION OF FLOW SHALL BE EMBOSSED ON THE TOP SURFACE OF EACH GRATE. LETTERING TO BE RECESSED 1/16".
- 2. MATERIAL SHALL BE IN ACCORDANCE WITH DIVISION 9 OF THE STANDARD SPECIFICATIONS "METAL FRAME AND GRATE FOR CATCH BASINS OR INLETS.
- 3. THE MATERIAL USED FOR THE GRATE SHALL BE DESIGNATED BY EMBOSSING EITHER DI (FOR DUCTILE IRON) OR CS (FOR CAST STEEL) NEAR THE NAME OF THE MANUFACTURER.
- 4. DIMENSIONS SHALL HAVE A $\pm 1/16$ " TOLERANCE, EXCEPT AS NOTED.
- 5. EDGES SHALL HAVE 1/8" RADIUS, 1/8" CHAMFER, OR COMPLETE DEBURRING.
- 6. THE FRAME SHALL BE MANUFACTURED IN ACCORDANCE WITH STANDARD PLAN B-2A
- 7. WELDING IS NOT PERMITTED.
- 8. AS AN ALTERNATE, 8 PADS 1-1/2"X 3/4"X 1/8", INTEGRALLY CAST WITH THE GRATE MAY BE USED.
- 9. MATERIAL MUST DESIGNATE D.I., DUCT. OR N.O.D.
- 10. GRATES SHALL NOT REFERENCE ANY JURISDICTION EXCEPT THE CITY OF REDMOND.




SECTION C-C









VANED GRATE FOR CATCH BASIN AND INLET

APPROVED: _ JON C. SPANGLER

APRIL 20, 2000 REV. DATE:

STORMWATER DIVISION





STANDARD DETAILS

VANED GRATE FOR CATCH BASIN AND INLET

FILE SD6619.DWG DRAWING NO.

619